



Permatie Interlocking Pin Specification

Permatie

Product Code: 1700102

The Skeletank permatie interlocking pin is required to join adjacent HPSC units. The permatie fits into the triangular opening on the end of the HPSC unit.

The permatie is tapered and designed to produce a tight joint. The permatie can only be inserted into the triangular opening on the HPSC unit with the 'holes' end inserted first. The holes are present to prevent the acculation of water.

Only 1 permatie per HPSC unit is required.



Technical Specification	
Material	Polypropylene core
Ultimate tensile joint strength per 1mm	126kN/m ²
Bending resistance of single joint	0.16 kNm
Colour	Grey
Nominal size	46 x 38 x 75mm deep
Weight	30g

Disclaimer

This product specification is neither giving nor implying warranty for the use of this information for design and installation, as these are beyond our control. The data provided is typical and based upon the mean values obtained from the samples taken for any one test. If not otherwise indicated the test procedures reflect usually the mean of five samples. Skeletank Limited reserve the right to change the specifications without prior notice. Skeletank® is a trade mark registered by Skeletank Limited.

Skeletank Limited,
Stormer Hill Works, Tottington,
Bury, Lancashire
BL8 4AT

Telephone: 0845 177 1535
Fax: 01204 885533
E-Mail: sales@skeletank.co.uk
Web: www.skeletank.co.uk